

(12) International Application Status Report

Received at International Bureau: 12 October 2004 (12.10.2004)

Information valid as of: Not available

(10) Publication number:
WO2005/028977

(43) Publication date:
31 March 2005 (31.03.2005)

(26) Publication language:
English (EN)

(21) Application Number:
PCT/AU2004/001319

(22) Filing Date:
24 September 2004 (24.09.2004)

(25) Filing language:
English (EN)

(31) Priority number(s):
2003905237 (AU)

(31) Priority date(s):
25 September 2003 (25.09.2003)

(31) Priority status:
Priority document received (in compliance
with PCT Rule 17.1)

(51) International Patent Classification:
C10F 5/00 (2006.01); F26B 17/12 (2006.01); **F26B 21/08** (2006.01)

(71) Applicants:
MADDINGLEY COLDRIY PTY LTD [AU/AU]; 20-30 Baldwin Road Altona North, Victoria 3025 (AU) (for all designated states except US)
WILSON, David [AU/AU]; 3 Oakbank Street Newport, Victoria 3015 (AU) (for US only)

(72) Inventors:
WILSON, David; 3 Oakbank Street Newport, Victoria 3015 (AU)

(74) Agent(s):
ROBERTS, Mark, K. ; Davies Collison Cave 1 Nicholson Street Melbourne, Victoria 3000 (AU)

(54) Title (EN): DRYER, DRYING METHOD AND DRYING PLANT

(54) Title (FR): SECHOIR, PROCEDE DE SECHAGE ET INSTALLATION DE SECHAGE

(57) Abstract:

(EN): The invention provides a dryer for drying particulate material, comprising at least one substantially vertical elongate container having an upper inlet (56a, 56b) for receiving a charge of moisture containing particulate material; a lower outlet (22) for discharging dried particulate material, whereby said particulate material travels under the influence of gravity from said inlet to said outlet; at least one substantially vertical gas permeable wall (20a, 20b) through which a drying gas can pass to contact said particulate material; said dryer also comprising at least one plenum (48, 50) on an exterior surface of said at least one gas permeable wall, covering ingress (38a) and egress openings within said at least one gas permeable wall.

(FR): L'invention concerne un séchoir destiné à sécher une matière particulaire, et comprenant au moins un récipient allongé sensiblement vertical possédant une entrée supérieure (56a), 56b) destinée à recevoir une charge de matière particulaire contenant de l'eau, une sortie inférieure (22) destinée à évacuer la matière particulaire séchée, cette matière particulaire se déplaçant sous l'action de la pesanteur depuis l'entrée jusqu'à la sortie, et au moins une paroi perméable au gaz sensiblement verticale (20a, 20b) à travers laquelle un gaz de séchage peut passer de sorte à venir au contact de la matière particulaire. Ledit séchoir comprend également au moins un plénum (48, 50) situé sur une surface extérieure de cette paroi perméable au gaz et recouvrant des ouvertures d'entrée (38a) et de sortie formées dans ladite paroi perméable au gaz.

International search report:
Received at International Bureau: 08 November 2004 (08.11.2004) [AU]

International preliminary examination report:
Chapter II demand received: 04 July 2005 (04.07.2005)

(81) Designated States:

ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NC, Z, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

European Patent Office (EPO) : AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR

African Intellectual Property Organization (OAPI) : BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG

African Regional Intellectual Property Organization (ARIPO) : BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW

Eurasian Patent Organization (EAPO) : AM, AZ, BY, KG, KZ, MD, RU, TJ, TM